



M4 Series RO

Medical Device

Reverse Osmosis System 60 Hz 2,200 to 13,200 GPD

Our M-series RO machines are designed for durable operation, high quality product water production, easy installation and straightforward control.

In addition, the M4 Series Reverse Osmosis System is manufactured in an FDA registered facility.

Standard Economy Features

- ■ Low-energy design reduces electrical requirements and operating costs
- ■ 5-micron pre-filter
- ■ Automatic inlet shut-off valve
- ■ Permeate and concentrate flow meters
- ■ Remote machine on/off capability
- ■ Thermal motor protection
- ■ Pre/Post-filter, primary, and final pressure gauges
- ■ Flow control center including concentrate and recycle valves
- ■ Autoflush system
- ■ Low inlet pressure switch
- ■ Digital conductivity meter
- ■ Alarms: Low inlet pressure, motor starter overload
- ■ Chemically compatible with 1% Minncare[®] Cold Sterilant disinfectant solution

Operating Parameters

- ■ Operating Pressure: 100–140 psi (6.9–7.6 bar)
- ■ Maximum Recovery: 75%
- ■ Nominal Rejection: 95–98%
- ■ Design Temperature: 77°F (25°C)
- ■ Operating Temperature: 55–85°F (13–30°C)
- ■ Minimum Inlet Pressure: 30 PSI (2 bar)

Materials of Construction

- ■ Welded Frame: Powder-Coated Carbon Steel
- ■ Membrane Elements: 4x40 TFC
- ■ Membrane Housing: Stainless Steel
- ■ Inlet Plumbing: Sch. 80 PVC
- ■ High Pressure Plumbing: Reinforced Rubber Hose
- ■ Permeate/Concentrate Tubing: Polyethylene, NSF
- ■ Control Enclosure: NEMA 1
- ■ Motor Starters: NEMA 4X
- ■ Cartridge Filter: 5 micron, 20 inch (51 cm)

Pump and Motor

- ■ Pump: Multi-Stage, Centrifugal Pump SS Shell/Housings Noryl* Internals SS Inlet/Discharge Castings
- ■ Motor: 3-Phase, TEFC, 208–230/460 VAC, 1-Phase, TEFC, 220 VAC (2200 and 4400 Models Only)

M4 60 Hz Specifications

Model	M4-2200	M4-4400	M4-6600	M4-8800	M4-11000	M4-13200
Part Number						
208VAC	1235775	1235778	1235781	1235794	1235797	1235800
230VAC	1235776	1235779	1235792	1235795	1235798	1235801
460VAC	1235777	1235780	1235793	1235796	1235799	1235802
Recovery Rate						
	50-75%	50-75%	50-75%	50-75%	50-75%	50-75%
Permeate Rate						
gpm	1.5	3	4.5	6	7.5	9
L/m	5.7	11.4	17.0	22.7	28.4	34.1
Concentrate Rate						
gpm	1.5-0.5	3-1	4.5-1.5	6-2	7.5-2.5	9-3
L/m	5.7-1.9	11.4-3.8	17.0-5.7	22.7-7.6	28.4-9.5	34.1-11.4
Pump and Motor						
HP (KW)	1.5 (1.1)	1.5 (1.1)	1.5 (1.1)	1.5 (1.1)	2 (1.5)	2 (1.5)
	SS1809X	SS1809X	SS1809X	SS1809X	SS1812X	SS1812X
Membrane Elements						
Number of	1	2	3	4	5	6
Array	1	1-1	1-1-1	1-1-1-1	2-1-1-1	2-2-1-1
Piping Inch (cm)						
Inlet	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)
Permeate	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)
Concentrate	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)	0.75 (1.9)
Approximate Overall Dimensions Inch (cm)						
Height	50 (127)	50 (127)	55 (139)	55 (139)	60 (152)	60 (152)
Width	30 (76)	30 (76)	30 (76)	30 (76)	30 (76)	30 (76)
Depth	20 (51)	20 (51)	20 (51)	26 (66)	26 (66)	26 (66)
Approximate Shipping Weight						
lbs (kg)	170 (77)	185 (83)	215 (98)	235 (107)	325 (147)	345 (156)

For more information contact Mar Cor Purification.

Mar Cor Purification
4450 Township Line Road
Skipack, PA 19474-1429
U.S.A.
Tel: (484) 991-0220
Toll Free: (800) 346-0365
Fax: (484) 991-0230

Mar Cor Purification
14550 28th Avenue North
Plymouth, MN 55447
U.S.A.
Toll Free: (800) 633-3080

Mar Cor Purification
3250 Harvester Road - Unit 6
Burlington, ON L7N 3W9
Canada
Tel: (905) 639-7025
Toll Free: (800) 268-5035
Fax: (905) 639-0425

Minntech B.V.
Sourethweg 11
6422 PC Heerlen
The Netherlands
Tel: (+31) 45 5471 471
Fax: (+31) 45 5429 695

Minntech Asia/Pacific Pte. Ltd.
438 Alecandra Road
#03-01 Alexandra Point
Singapore 119958
Tel: (+65) 6227 9698
Fax: (+65) 6225 6848