



3300 Series RO

Reverse Osmosis System 60 Hz 2,200 to 3,300 GPD

The Biolab 3300 Series Reverse Osmosis Systems are designed to produce up to 2.29 USgpm (8.63 lpm) of pure water. The 3300 Series provides high quality product water, user-friendly controls, durable construction, and easy installation. All systems are built to exacting standards under ISO 9001:2000.

Operating Parameters

- Operating Pressure: 225 psig (1551 KPA)
- Maximum Recovery: 75%
- Nominal Rejection: 95-98%
- Operating Temperature: 35-95° F (2-35° C)
- Minimum Inlet Pressure: 30 psig (210 KPA)
- Design Temperature: 77° F (25° C)

Materials of Construction

- Frame: Epoxy coated steel
- Membrane Elements: TF Polyamide
- Membrane Housing: 304L Stainless Steel
- Low Pressure Pipe: Sch. 80 PVC/Polypropylene
- High Pressure Pipe: Polypropylene
- Control Enclosure: NEMA 4/12
- Pump: Brass

Typical Medical Applications

- Commercial water
- Research and laboratory use
- Boiler feed water
- Humidification systems
- Process ingredient water
- Rinse water
- Ion exchange pre-treatment
- Car wash rinse water

Standard Features

- 1.0 - micron FiberFlo Hollow Fiber pre-filter
 - Automatic inlet shut-off valve
 - Rotary vane pump 1 phase
 - Three variable flow meters
 - Auto-flush feature
 - Analog system control
 - Adjustable reject recirculation
 - Pre-filter, post filter, and pressure gauges
 - Single source power
 - Optional conductivity meter
-

3300 60 Hz Specifications @ 25°C

Model Number	Stock Number	Permeate gpm (lpm)	Concentrate gpm (lpm)	Motor hp	Elements Number	Inlet in (mm)	Permeate in (mm)	Concentrate in (mm)	Weight lbs (kg)
3300-2K	26C15F-1RO	1.53 (5.79)	0.38 (1.44)	1	2	3/4 (1.91)	1/2 (3.81)	1/2 (1.27)	174 (79)
3300-3K	36C15F-1RO	2.29 (8.66)	0.57 (2.16)	1	3	3/4 (1.91)	1/2 (3.81)	1/2 (1.27)	185 (84)

Note: All weights and dimensions are approximate.

Feed Water Requirements*

Feed Water Source	Potable Tap
Maximum Silt Density Index	< 3
Maximum Free Chlorine	< 0.1 ppm
Operating Temperature Range	2-35° C
.....	(35-95° F)
Operating pH Range	2-11
Total Dissolved Solids	< 1,000 ppm
Softened or Langelier Index	< 0.5
Iron / Manganese	< 0.1 ppm

*If any of the feed water requirements are not within the limits given, consult one of our application specialists for assistance.

System Dimensions

42" high x 24" wide x 18" deep

Common Specifications

Standard Product Ordering Information

Biolab 3300 RO Stock Number Matrix

Number of RO Elements

2 3

Membrane Type

6 - TF Polyamide

Application Type

C - Commercial & Industrial

Housing Type

1 - 304 SS

Electrical Requirements

5 - 115/1/60

Pump Type

F - Brass

Controller Options

1 - Analog no conductivity 4 - Digital product conductivity

Unit Type

RO - Reverse Osmosis System

3	6	C	1	5	F	-	1	RO
---	---	---	---	---	---	---	---	----

Installation Considerations

- For proper serviceability, there should be 18" of space around the system. This includes front, back, and sides.
- The system should be installed on a firm, level surface and have a drain with suitable capability to handle concentrate.
- Minimum dynamic operating pressure of 30 psig is required for proper system operation. The max pressure is 90 psig.

Mar Cor Purification
4450 Township Line Road
Skipack, PA 19474-1429
U.S.A.
Tel: (484) 991-0220
Toll Free: (800) 346-0365
Fax: (484) 991-0230

Mar Cor Purification
14550 28th Avenue North
Plymouth, MN 55447
U.S.A.
Toll Free: (800) 633-3080

Mar Cor Purification
3250 Harvester Road - Unit 6
Burlington, ON L7N 3W9
Canada
Tel: (905) 639-7025
Toll Free: (800) 268-5035
Fax: (905) 639-0425

Minntech B.V.
Sourethweg 11
6422 PC Heerlen
The Netherlands
Tel: (+31) 45 5471 471
Fax: (+31) 45 5429 695

Minntech Asia/Pacific Pte. Ltd.
438 Alecandra Road
#03-01 Alexandra Point
Singapore 119958
Tel: (+65) 6227 9698
Fax: (+65) 6225 6848